

Model: AE4460Y-FZ1C

Product Description

Type:	Reciprocating Compressors
Application:	HBP - High Back Pressure
ProductDescription:	R-134a
Voltage/Frequency:	220-240V ~ 50Hz
Version:	N/A



Product Specifications

Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power (l) W	(E) Efficiency			EVAP TEMP	Condition	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		(R) Btu/h	(R) kcal/h	(R) W		(E) Btu/Wh	(E) kcal/Wh	W/W					
ASHRAE	220V ~ 50HZ	5250	1323	1539	667	7.87	1.98	2.31	7.2°C (45°F)	54°C (130°F)	35°C (95°F)	35°C (95°F)	46°C (115°F)
ASHRAE	240V ~ 50HZ	5250	1323	1539	684	7.68	1.93	2.25	7.2°C (45°F)	54°C (130°F)	35°C (95°F)	35°C (95°F)	46°C (115°F)

General

Evaporating Temp. Range:	-15°C to 15°C (5°F to 59°F)
Motor Torque:	High Start Torque (HST)
Compressor Cooling:	Fan

Mechanical

Weight:	11
Weight Unit of Measure:	KG
Displacement (cc):	15.09
Oil Type:	Polyolester
Viscosity (cSt):	32
Oil Charge (cc):	387

Electrical

Voltage Range (50 Hz):	198-253
Voltage Range (60 Hz):	
Locked Rotor Amps (LRA):	18
Rated Load Amps (RLA 50 Hz):	3.96
Rated Load Amps (RLA 60 Hz):	0
Max. Continuous Current (MCC in Amps):	0
Motor Resistance (Ohm) - Main:	4.09
Motor Resistance (Ohm) - Start:	20.81
Motor Type:	CSIR
Overload Type:	
Relay Type:	

Agency Approval

CCC Listed, CE Listed, GOST RUSSIA Listed, GOST UKRAINE Listed, TIS Listed, VDE Listed