

**Model: AGB4573TTZ**
**Product Description**

**Type:** Reciprocating Compressors  
**Application:** HBP - High Back Pressure  
**ProductDescription:** R-22  
**Voltage/Frequency:** 440V 3~ 60Hz 400V 3~ 50Hz  
**Version:** N/A


**Product Specifications**
**Performance**

Condition	Test Voltage	Refrigeration Capacity			Input Power (I) W	(E) Efficiency			EVAP TEMP	Condition	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		(R) Btu/h	(R) kcal/h	(R) W		(E) Btu/Wh	(E) kcal/Wh	W/W					
EN12900	440V 3~ 60HZ	35341	8906	10355	4783	7.39	1.86	2.16	-10°C (14°F)	45°C (113°F)	32°C (90°F)	0°C (32°F)	45°C (113°F)
EN12900	400V 3~ 50HZ	29809	7512	8734	4029	7.4	1.86	2.17	-10°C (14°F)	45°C (113°F)	32°C (90°F)	0°C (32°F)	45°C (113°F)

**General**

**Evaporating Temp. Range:** -6.7°C to 12.8°C (20°F to 55°F)  
**Motor Torque:** High Start Torque (HST)  
**Compressor Cooling:** Fan

**Mechanical**

**Weight:** 49  
**Weight Unit of Measure:** KG  
**Displacement (cc):** 135  
**Oil Type:** Mineral  
**Viscosity (cSt):** 68  
**Oil Charge (cc):** 1960

**Electrical**

**Voltage Range (50 Hz):** 340-440  
**Voltage Range (60 Hz):** 396-499  
**Locked Rotor Amps (LRA):** 61  
**Rated Load Amps (RLA 50 Hz):** 10.8  
**Rated Load Amps (RLA 60 Hz):** 11.8  
**Max. Continuous Current (MCC in Amps):** 0

<b>Motor Resistance (Ohm) - Main:</b>	2.2
<b>Motor Resistance (Ohm) - Start:</b>	2.2
<b>MotorType:</b>	3PH
<b>Overload Type:</b>	
<b>Relay Type:</b>	

## Agency Approval

CCC Listed, CE Listed, GOST RUSSIA Listed, GOST UKRAINE Listed, IRAM Listed