

Model: AJE4461YFZ

Product Description

Type:	Reciprocating Compressors
Application:	HBP - High Back Pressure
ProductDescription:	R-134a
Voltage/Frequency:	220-240V ~ 50Hz
Version:	N/A



Product Specifications

Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power (I) W	(E) Efficiency			EVAP TEMP	Condition	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		(R) Btu/h	(R) kcal/h	(R) W		(E) Btu/Wh	(E) kcal/Wh	W/W					
EN12900	230V ~ 50HZ	5205	1312	1525	620	8.4	2.12	2.46	5°C (41°F)	45°C (113°F)	32°C (90°F)	15°C (59°F)	45°C (113°F)

General

Evaporating Temp. Range:	-15°C to 15°C (5°F to 59°F)
Motor Torque:	High Start Torque (HST)
Compressor Cooling:	Fan

Mechanical

Weight:	20
Weight Unit of Measure:	KG
Displacement (cc):	18.3
Oil Type:	Polyolester
Viscosity (cSt):	32
Oil Charge (cc):	782

Electrical

Voltage Range (50 Hz):	198-253
Voltage Range (60 Hz):	
Locked Rotor Amps (LRA):	19
Rated Load Amps (RLA 50 Hz):	4
Rated Load Amps (RLA 60 Hz):	0
Max. Continuous Current (MCC in Amps):	5.9
Motor Resistance (Ohm) - Main:	3.9

Motor Resistance (Ohm) - Start:
Motor Type:

20.6
CSIR

Overload Type:

Relay Type:

Agency Approval

CE Listed, GOST RUSSIA Listed, GOST UKRAINE Listed, VDE Listed