

## Model: AJE4517EHZ

### Product Description

<b>Type:</b>	Reciprocating Compressors
<b>Application:</b>	HBP - High Back Pressure
<b>ProductDescription:</b>	R-22
<b>Voltage/Frequency:</b>	208-220V ~ 60Hz
<b>Version:</b>	N/A



### Product Specifications

#### Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power (I) W	(E) Efficiency			EVAP TEMP	Condition	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		(R) Btu/h	(R) kcal/h	(R) W		(E) Btu/Wh	(E) kcal/Wh	W/W					
EN12900	220V ~ 60HZ	14754	3718	4323	1578	9.35	2.36	2.74	5°C (41°F)	45°C (113°F)	32°C (90°F)	15°C (59°F)	45°C (113°F)

#### General

<b>Evaporating Temp. Range:</b>	-15°C to 15°C (5°F to 59°F)
<b>Motor Torque:</b>	High Start Torque (HST)
<b>Compressor Cooling:</b>	Fan

#### Mechanical

<b>Weight:</b>	23
<b>Weight Unit of Measure:</b>	KG
<b>Displacement (cc):</b>	25.95
<b>Oil Type:</b>	Mineral
<b>Viscosity (cSt):</b>	68
<b>Oil Charge (cc):</b>	782

#### Electrical

<b>Voltage Range (50 Hz):</b>	
<b>Voltage Range (60 Hz):</b>	187-242
<b>Locked Rotor Amps (LRA):</b>	45
<b>Rated Load Amps (RLA 50 Hz):</b>	8.5
<b>Rated Load Amps (RLA 60 Hz):</b>	8.5
<b>Max. Continuous Current (MCC in Amps):</b>	0
<b>Motor Resistance (Ohm) - Main:</b>	1.2

Motor Resistance (Ohm) - Start:  
Motor Type:

6.1  
CSR

Overload Type:

Relay Type:

## Agency Approval

CE Listed