

**Model: THB4428ZFZ**
**Product Description**

**Type:** Reciprocating Compressors  
**Application:** HBP - High Back Pressure  
**ProductDescription:** R-404A  
**Voltage/Frequency:** 220-240V ~ 50Hz  
**Version:** N/A


**Product Specifications**
**Performance**

Condition	Test Voltage	Refrigeration Capacity			Input Power (I) W	(E) Efficiency			EVAP TEMP	Condition	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		(R) Btu/h	(R) kcal/h	(R) W		(E) Btu/Wh	(E) kcal/Wh	W/W					
ASHRAE	230V ~ 50HZ	2560	645	750	433	5.91	1.49	1.73	7.2°C (45°F)	54°C (130°F)	35°C (95°F)	35°C (95°F)	46°C (115°F)
CECOMAF	230V ~ 50HZ	2040	514	598	424	4.81	1.21	1.41	5°C (41°F)	55°C (131°F)	32°C (90°F)	32°C (90°F)	55°C (131°F)

**General**

**Evaporating Temp. Range:** -15°C to 15°C (5°F to 59°F)  
**Motor Torque:** High Start Torque (HST)  
**Compressor Cooling:** Fan

**Mechanical**

**Weight:** 8  
**Weight Unit of Measure:** KG  
**Displacement (cc):** 5  
**Oil Type:** Polyolester  
**Viscosity (cSt):** 32  
**Oil Charge (cc):** 336.2

**Electrical**

**Voltage Range (50 Hz):** 198-253  
**Voltage Range (60 Hz):**  
**Locked Rotor Amps (LRA):** 13  
**Rated Load Amps (RLA 50 Hz):** 2.87  
**Rated Load Amps (RLA 60 Hz):** 0  
**Max. Continuous Current (MCC in Amps):** 0

Motor Resistance (Ohm) - Main: 7.05  
Motor Resistance (Ohm) - Start: 24.55

MotorType: CSIR

Overload Type:

Relay Type:

## Agency Approval

CE Listed, VDE Listed