

Model Nomenclature (Example: ASHR9440ZNP1)

CU Family	Product Type	Compressor	Application Range	Nominal Capacity R404A	Refrigerant	Power Supply	Unit Configuration (Application)	Factory Installed Options	Generation
AS	H	R	9	440	Z	NA	M	P	1
AS	H (Outdoor - Remote) N (Indoor - Remote)	S (Scroll) R (Recip)	9 (Medium) 2 (Low)	First number is total digits. Remainder is capacity in Btu/h. This example; 4,000 Btu/h	R-404A R-448A R-449A R-452A	AA (115V/60Hz/1) NA (208-230V/60Hz/1) FA (208-230V/60Hz/3)	M (microchannel with PSC fan motor) F (tube and fin with PSC fan motor) N (microchannel with high efficiency, EC fan motor) H (tube and fin with high efficiency, EC fan motor)	S Silver P Platinum G Gold C Custom	1 (1st)

Pre-configured Feature Sets

Outdoor Condensing Unit – Medium Temperature

FEATURES	ARGUS Silver	ARGUS Platinum	ARGUS Gold
Service Valves	X	X	X
Crankcase Heater	X	X	X
Adjustable Low Pressure Control			X
Fixed Low Pressure Switch	X	X	
High Pressure Switch	X	X	X
Receiver Tank	X	X	
Receiver Tank (Heated and Insulated)			X
Liquid Line Filter Drier		X	X
Sight Glass		X	X
Discharge Check Valve			X
Accumulator (Insulated)			X
Suction Line Filter			X
Head Pressure Control	X	X	X
Electomechanical Defrost Timer		X	X
Pre-Painted Enclosure	X	X	X
LED Light in Service Panel	X	X	X
QR Code (Service Parts/Wiring Diagram)	X	X	X

Indoor Condensing Unit – Medium Temperature

FEATURES	ARGUS Silver	ARGUS Platinum	ARGUS Gold
Service Valves	X	X	X
Crankcase Heater			
Adjustable Low Pressure Control			X
Fixed Low Pressure Switch	X	X	
High Pressure Switch	X	X	X
Receiver Tank	X	X	X
Receiver Tank (Heated and Insulated)			
Liquid Line Filter Drier		X	X
Sight Glass		X	X
Discharge Check Valve			X
Accumulator (Insulated)			X
Suction Line Filter			X
Head Pressure Control			
Electomechanical Defrost Timer		X	X
Pre-Painted Enclosure	X	X	X
LED Light in Service Panel	X	X	X
QR Code (Service Parts/Wiring Diagram)	X	X	X

Outdoor Condensing Unit – Low Temperature

FEATURES	ARGUS Silver	ARGUS Platinum	ARGUS Gold
Service Valves	X	X	X
Crankcase Heater	X	X	X
Adjustable Low Pressure Control	X	X	X
High Pressure Switch	X	X	X
Receiver Tank	X	X	
Receiver Tank (Heated and Insulated)			X
Liquid Line Filter Drier		X	X
Sight Glass		X	X
Discharge Check Valve	X	X	X
Accumulator (Insulated)		X	X
Suction Line Filter			X
Head Pressure Control	X	X	X
Electomechanical Defrost Timer		X	X
Pre-Painted Enclosure	X	X	X
LED Light in Service Panel	X	X	X
QR Code (Service Parts/Wiring Diagram)	X	X	X

Indoor Condensing Unit – Low Temperature

FEATURES	ARGUS Silver	ARGUS Platinum	ARGUS Gold
Service Valves	X	X	X
Crankcase Heater			
Adjustable Low Pressure Control	X	X	X
High Pressure Switch	X	X	X
Receiver Tank	X	X	X
Receiver Tank (Heated and Insulated)			
Liquid Line Filter Drier		X	X
Sight Glass		X	X
Discharge Check Valve	X	X	X
Accumulator (Insulated)		X	X
Suction Line Filter			X
Head Pressure Control			
Electomechanical Defrost Timer		X	X
Pre-Painted Enclosure	X	X	X
LED Light in Service Panel	X	X	X
QR Code (Service Parts/Wiring Diagram)	X	X	X

3 phase units on Platinum and Gold feature sets include a phase monitor.
Refer to Tecumseh's Remote Condensing Unit Installation Instructions for Head Pressure Control Settings.
Start components for scroll condensing units on platinum and gold outdoor.