



Tecumseh

Lo-Profile Unit Coolers

**NEW
PRODUCT**

▶ The Perfect Complement to Tecumseh's Silver, Platinum, and Gold Gen III Outdoor Condensing Units

▶ Save Money and Increase Energy Efficiency with EC Motor Technology



Improved Performance

- ▶ High Efficiency ECM Motor (115-230V 50/60HZ)
- ▶ 12" Fan Blades for More CFM and Longer Air Throw
- ▶ Venturi Style Distributor for Wide Application Range
- ▶ Optimized Coil Design
- ▶ Defrost Heater Improvements
- ▶ New Coil Circuitry and Improved Fin Surface Design

Easy to Service & Install

- ▶ Motors are Serviceable through Fan Guards
- ▶ Hub Mounted Fan Blade for Quick Change Out
- ▶ Easy Access Front Corner Panels
- ▶ Standard Footprint for Easy Replacement
- ▶ Industry Standard 3/4" MPT Drain Fitting
- ▶ Wiring for Liquid Line Solenoid Included

For more information visit www.tecumseh.com



Medium Temperature – Air Defrost

Item No.	Model No.	BTU/Hr @10°TD	CFM	No. of Fans	EC Motor Amps		Connections* Suction OD (in)	Dimensions (in) H = 15.25, D=14.75, W=	Weight (lb)
					115V	230V			
6745	PLPH-410A	4100	730	1	0.6	0.3	5/8	29.25	37
6745002	PLPH-530A	5300	700	1	0.6	0.3	5/8	29.25	40
6745004	PLPH-660A	6600	650	1	1.2	0.6	7/8	29.25	43
6744	PLPH-710A	7100	1460	2	1.2	0.6	7/8	45.25	54
6744002	PLPH-910A	9100	1400	2	1.2	0.6	7/8	45.25	57
6744008	PLPH-1050A	10500	1400	2	1.2	0.6	7/8	45.25	58
6744004	PLPH-1210A	12100	1400	2	1.2	0.6	7/8	45.25	60
6744006	PLPH-1310A	13100	1300	2	1.8	0.9	7/8	45.25	62
6747	PLPH-1410A	14100	2100	3	1.8	0.9	7/8	61.25	72
6747002	PLPH-1570A	15700	2100	3	1.8	0.9	7/8	61.25	76
6747004	PLPH-1810A	18100	1950	3	1.8	0.9	7/8	61.25	78
6749	PLPH-2090A	20900	2800	4	2.4	1.2	1 1/8	77.25	91
6751	PLPH-2610A	26100	3500	5	3.0	1.5	1 1/8	93.25	112
6753	PLPH-3130A	31300	4200	6	3.6	1.8	1 1/8	109.25	133
6753002	PLPH-3710A	37100	3900	6	3.6	1.8	1 3/8	109.25	136

Low Temperature – Electric Defrost

Item No.	Model No.	BTU/Hr @10°TD	CFM	No. of Fans	EC Motor Amps		Electric Heater Amps		Connections* Suction OD (in)	Dimensions (in) H = 15.25, D=14.75, W=	Weight (lb)
					230V	230V/1PH	230V/3PH	460V/1PH			
6746	PLPH-360E	3600	700	1	3.9	3.9	2.3	2.0	5/8	29.25	33
6746002	PLPH-410E	4100	700	1	3.9	3.9	2.3	2.0	5/8	29.25	35
6746004	PLPH-480E	4800	650	1	3.9	3.9	2.3	2.0	5/8	29.25	38
6999	PLPH-660E	6600	1400	2	7.8	7.8	4.5	3.9	5/8	45.25	52
6999002	PLPH-760E	7600	1400	2	7.8	7.8	4.5	3.9	5/8	45.25	54
6999004	PLPH-910E	9100	1300	2	7.8	7.8	4.5	3.9	7/8	45.25	57
6748	PLPH-1210E	12100	2100	3	11.7	11.7	6.8	5.9	7/8	61.25	69
6748002	PLPH-1410E	14100	1950	3	11.7	11.7	6.8	5.9	7/8	61.25	71
6750	PLPH-1610E	16100	2800	4	15.7	15.7	9.0	7.8	1 1/8	77.25	90
6750002	PLPH-1810E	18100	2600	4	15.7	15.7	9.0	7.8	1 1/8	77.25	93
6752	PLPH-2010E	20100	3500	5	19.6	19.6	11.3	9.8	1 1/8	93.25	110
6754	PLPH-2410E	24100	4200	6	23.5	23.5	13.6	11.7	1 1/8	109.25	130
6754002	PLPH-2810E	28100	3900	6	23.5	23.5	13.6	11.7	1 1/8	109.25	133

*All Inlet Connections are 1/2" OD

*All Drain Connections are 3/4" MPT